

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Withdrawn) A laundry device comprising:
a body;
a drum provided in the body, thereon a circumferential surface a plurality of holes having each diameter of less than 1mm being formed; and
a motor driven for rotating the drum at high speed of at least and more 2000RPM.
2. (Withdrawn) The laundry device as claimed in claim 1, wherein at least one and more holes having each diameter of more than 1mm are further formed on a circumferential surface of the drum.
3. (Withdrawn) The laundry device as claimed in claim 2, wherein the number of holes having each diameter of more than 1mm is smaller than the number of holes having each diameter of less than 1mm.
4. (Withdrawn) The laundry device as claimed in claim 1, wherein the drum is installed more inclined downward coming along from a front surface to a rear surface, and at least one and more holes having each diameter of more than 1mm may be formed on a front circumferential surface.
5. (Withdrawn) The laundry device as claimed in claim 1, wherein the drum is installed thereof an opening for introduction of laundry facing an upper part and on an upper circumferential surface at least one and more holes having each diameter of more than 1mm are formed.
6. (Withdrawn) The laundry device as claimed in claim 1, wherein the motor is driven for rotating the drum at high speed of 3000~4000RPM.

7. (Withdrawn) The laundry device as claimed in claim 1, further comprising a steam supply part in the body for spraying high temperature steam into the drum.

8. (Withdrawn) The laundry device as claimed in claim 1, further comprising a detergent supply part in the body for spraying fluid detergent in spray state into the drum.

9. (Withdrawn) The laundry device as claimed in claim 1, further comprising a washing water spray part in the body for spraying washing water into the drum.

10. (Currently Amended) A method for operating a laundry device comprising:
a ~~(a) step for~~ supplying steam to an inside of a drum where the laundry is introduced to soak the laundry and contaminants of the laundry;
a ~~(b) step for~~ stopping the steam supply after a predetermined period of time; and
a ~~(c) step for centrifugally separating~~ rotating the drum at a high speed to separate centrifugally the contaminants soaked with the steam from the laundry ~~by rotating the drum at high speed.~~

11. (Currently Amended) The method for operating a laundry device as claimed in 10, wherein the temperature of the supplied steam ~~supplied in the (a) step~~ is higher than a temperature at which the laundry ~~may be~~ is sterilized.

12. (Currently Amended) The method for operating a laundry device as claimed in 10, wherein the predetermined period of time ~~in the (b) step~~ is the time when the laundry ~~may be~~ is soaked ~~by the steam~~ fully.

13. (Currently Amended) The method for operating a laundry device as claimed in 10, wherein the rotation speed ~~in the (c) step~~ is 2000~4000RPM.

14. (Currently Amended) The method for operating a laundry device as claimed in 10, further comprising a ~~(d) step alternately operated with the (c) step at relatively lower speed than the rotation speed in the (c) step for discharging steam in the drum~~ rotating the drum

alternately at a lower speed than the rotation speed for separation contaminants to discharge steam in the drum.

15. (Currently Amended) The method for operating a laundry device as claimed in 14, wherein the speed for ~~operating the (d) step~~ discharging steam is lower than 100RPM.

16. (Currently Amended) The method for operating a laundry device as claimed in 14, wherein the time for ~~operating the (d) step~~ rotating the drum for discharging steam is shorter than the time for rotating the drum ~~at high speed~~ for separating contaminants.

17. (Currently Amended) The method for operating a laundry device as claimed in 10, further comprising a ~~(e) step for~~ spraying washing water in the drum before ~~the steam in the (a) step is supplied~~ the steam supplying to the inside of the drum.

18. (Currently Amended) The method for operating a laundry device as claimed in 17, wherein the washing water sprayed ~~in the (e) step~~ is in cold water state not boiled.

19. (Currently Amended) The method for operating a laundry device as claimed in 17, further comprising a ~~(f) step for~~ spraying fluid detergent to the laundry before ~~the (e) step~~ the washing water spraying.

20. (Currently Amended) The method for operating a laundry device as claimed in 19, wherein the detergent supplied ~~in the (f) step~~ is concentrated detergent in fluid spray state.

21. (Currently Amended) The method for operating a laundry device as claimed in 19, further comprising a ~~(g) step for~~ rinsing the laundry by spraying steam or washing water in the drum after ~~the (f) step~~ the fluid detergent spraying.

22. (Currently Amended) The operating method of a laundry device as claimed in 10, wherein during the ~~(a) step~~ steam supplying ~~[[a]]~~ the drum is rotated at a ~~[[low]]~~ speed less than 100RPM.

23. (Withdrawn) A method for operating a laundry device comprising:
a (h) step for performing a washing cycle for a predetermined period of time;
a (i) step for performing at least one and more rising cycle when the (h) step is completed;
a (j) step for performing a final spinning cycle by rotating a drum at high speed when the (i) step is completed; and
a (k) step for performing a dry cycle by rotating the drum at higher speed than the speed in the final spinning cycle when the final spinning cycle is completed.
24. (Withdrawn) The method for operating a laundry device as claimed in 23, wherein the speed of the drum rotation in the (j) step is set up between 600RPM and 2000RPM.
25. (Withdrawn) The method for operating a laundry device as claimed in 23 wherein the speed of the drum rotation in the (k) step is set up between 3000 RPM and 4000 RPM.
26. (Withdrawn) The method for operating a laundry device as claimed in 23, further comprising a (l) step for supplying steam to the dried laundry in the drum when the (k) step is completed.
27. (Withdrawn) The method for operating a laundry device as claimed in 26, wherein the temperature of the steam supplied in the (l) step is higher than a temperature at which the laundry may be sterilized.
28. (Withdrawn) The operating method of a laundry device as claimed in 26, wherein the (l) step is performed for a predetermined period of time enough to refresh the laundry in the drum.
29. (Currently Amended) The method for operating a laundry device as claimed in 14, further comprising a (e) step for spraying washing water in the drum before the steam in the (a) step is supplied the steam supply to the inside of the drum.